



- NOTES**
- \* FACTORY MUTUAL APPROVED (FM)
  - \* MEETS OR EXCEEDS NFPA 58 AND 70 REQUIREMENTS
  - \* FOR OUTDOOR INSTALLATION, GENERAL PURPOSE LOCATION
  - \* DESIGN PRESSURE
  - HEAT EXCHANGER WAMP 250 PSIG @ 650F, MGMT -20F @ 250 PSIG
  - VAPOR INLET WAMP 250 PSIG @ 650F
  - MIXED GAS OUTLET WAMP 50 PSIG @ 650F
  - \* WATERBATH CAPACITY = 270 U.S. GALLONS
  - \* APPROXIMATE WEIGHT = 2,800 LBS
  - \* FREEZE AND CORROSION PROTECTION REQUIRED
  - \* EXTERIOR FINISH "BAM" DEK BLUE" AND BLACK POWDER COAT
  - \* DIMENSIONS SHOWN 4/16"

MODEL	OUTLET PRESSURE	REQUIRED ACCUMULATOR TANK CAPACITY	CAPACITY BTU/HR
QM65 D -10	10 PSIG	240 GAL.	88,000,000
-5	5 PSIG		
QM70 D -8	8 PSIG	70,000,000	
-12	12 PSIG		

**Sam Dick Industries**

1140 N.W. 48th ST. SEATTLE, WA 98107  
 TEL: (206) 786-5410 FAX: (206) 786-5414

Model: G. ROPPE Rev: 4-1-87  
 Material: NONE  
 Finish: B.D.I. STD.

PACKAGED VAPORIZING MIXING SYSTEM, MODELS QM65 D-10, QM70 D-5, QM70 D-8 & QM70LD-12

**0150-8008**

1 of 1